EXAMPLE JSA

JOB SAFETY ANALYSIS	JOB: Rotar	JOB: Sharpening & Replacing a Rotary Mower Blade		L	DATE: 1/1/2000
EXAMPLE		ITLE OF PERSON WHO DOES SUPERVIS JOB: John Yard Worker		OR: Jones	INDIVIDUAL PREPARING JSA: John Jones
DEPARTMENT: Maintenance Group REOUIRED AND/OR RECOMME	LOCATI		utificat:	ion	
REQUIRED AND/OR RECOMME PERSONAL PROTECTIVE EQU		Gloves	& Safety	Glasses	
SEQUENCE OF BASIC JOB STEPS		POTENTIAL ACCIDENTS OR HAZARDS		RECOMMENDED SAFE JOB PROCEDURI	
1. Disconnect spark pwire.	plug	1. Striking agai housing Burn hand			not use excessive Allow mower to cool.
 Remove gasoline. Invert mower. 		2. Spillage - Fire - Inhalation.		2. Ventilation. No smoking, proper container. Flush away with water (if necessary).	
3. Invert mower. 4. Remove dull blade. 5. Check for bent blade. 6. Sharpen & balance dull blade. 7. Reassemble blade to mower. 8. Return mower to cutting position. 9. Reconnect spark plug wire. 10. Add gasoline. 11. Operate mower.		3. Caught between (CB) Spilling gasoline Overexertion 4. Knuckles striking against blade. 5. None. 6. Cutting hand; striking against vice. 7. Striking against blade or housing. 8. Overexertion. 9. None. 10. Fire. 11. Normal operating hazards.		with water (if necessary). 3. Tip properly. (Grass catcher chute up). Be sure cap is tight. Lift properly, use leg muscles. 4. Secure block blade - wooden block. Use gloves. Use proper size socket wrench with extender. 5. None. 6. Wear gloves. Avoid contact with sharp blade. 7. Block blade. Wear gloves. Avoid contact with sharp blade. 8. Use leg muscles, not back. 9. None. 10. Ventilate. No smoking. Proper container. 11. Check for excessive vibration or unusual noise.	
EMPLOYEES ASSISTING 1	IN DEVE		A. STRIE B. CAUGE C. SLIP D. PUSH:	HT IN, BY , TRIP, OI ING, PULL:	NST OR BEING STRUCK BY , OR BETWEEN

JSA 1-00 STATE OF LOUISIANA